
























Номенклатура светофоров транспортных по ГОСТ 52282-2004

№ п/п	Индекс	Внешний вид	Конструкция	Сигнал светофора					-	-
										
				Диаметр (габаритные размеры) выходной апертуры						
1	Т.1		I	200	200	200	-	-		
			II	300	300	300				
			III		200	200				
2	Т.1.п		I	200	200	200	200	-		
			II	300	300	300	300			
			III		200	200	200			
3	Т.1.пк		I	200	200	200	200	-		
			II	300	300	300	300			
			III		200	200	200			
4	Т.1.л		I	200	200	200	200	-		
			II	300	300	300	300			
			III		200	200	200			
5	Т.1.лк		I	200	200	200	200	-		
			II	300	300	300	300			
			III		200	200	200			
6	Т.1.пл		I	200	200	200	200	-		
			II	300	300	300	300			
			III		200	200	200			

Номенклатура светофоров транспортных по ГОСТ 52282-2004

№ п/п	Индекс	Внешний вид	Конструкция	Сигнал светофора				
				Диаметр (габаритные размеры) выходной апертуры				
7	Т.1.плк		I	200	200	200	200	-
			II	300	300	300	300	
			III		200	200	200	
8	Т.1.г		I	200	200	200	-	-
			II	300	300	300	-	-
9	Т.1.1.р		I	200	200	200	200	-
			II	300	300	300	300	
			III	300	200	200	200	
10	Т.2		I	200	200	200	-	-
			II	300	300	300		
			III	-	200	200		
11	Т.3		I	100	100	100	100	-
12	Т.3.п		I	100	100	100	100	-
13	Т.3.л		I	100	100	100	100	-
14	Т.4		I	600x550	-	600x550	-	-
15	Т.4.Ж		I	600x550	600x550	600x550	-	-

Номенклатура светофоров транспортных по ГОСТ 52282-2004

№ п/п	Индекс	Внешний вид	Конструкция	Сигнал светофора				
								
				Диаметр (габаритные размеры) выходной апертуры				
16	Т.5		I	-	-	-	-	100
17	Т.6		I	200	-			
			II	300				
18	Т.6.Д		I	200	-			
			II	300				
16	Т.7		I	-	200	-		
			II		300			
17	Т.8		I	200	-	200	-	
			II	300	-	300		
18	Т.9		I	200	200	200	-	-
19	Т.10		I	-	-	-	-	200

Номенклатура светофоров пешеходных по ГОСТ 52282-2004

№ п/п	Индекс	Внешний вид	Конструкция	Сигнал светофора				
								
				Диаметр выходной апертуры				
1	П.1		I	200	-	200	-	
			II	300		300		
2	П.2		I	200x200	-	200x200	-	
			II	300x300		300x300		